

# MKT LEADS — COMPONENT LIST

DESCRIPTION	Part No. and Weight	
	20' Series	25' Series
<b>SWINGING TYPE LEAD — ESSENTIAL COMPONENTS</b>		
<b>BAIL ATTACHMENT (SHEAVED)</b>		
Mounts on Shaft at top of 15 ft. tapered section for connection of Crane Line. (Similar to E).	7200044 100 lbs.	7400031 220 lbs.
<b>BAIL ATTACHMENT (BASIC)</b>		
Mounts on Shaft at top of 15 ft. tapered section for connection of Crane Line. (Similar to F).	7990150 100 lbs.	7990146 220 lbs.
<b>15 FT. TAPERED SECTION</b>		
Attaches to Boom Point connector. Top of Section is tapered to clear boom. Equipped with upper hammer limit stop. (Similar to G).	7200022 1038 lbs.	7400022 1721 lbs.
<b>5 FT. STABBING POINT</b>		
Used at bottom end of Lead to position Lead on the ground. (Similar to J).	7200043 404 lbs.	7400030 744 lbs.
<p><b>NOTE —</b> Swinging type Lead also requires Intermediate Sections to obtain the desired length. When using this type Lead for driving Steel Sheet Piling a minimum length of 20 ft. for Steam-Air and 30 ft. for Diesel Hammers is recommended.</p>		
<b>INTERMEDIATE SECTIONS — ALL LEAD TYPES</b>		
<b>30 FT. INTERMEDIATE SECTION WITH LADDER</b>		
This Section may be used with all Lead types. (Similar to H).	7200033 2124 lbs.	7400024 3822 lbs.
<b>20 FT. INTERMEDIATE SECTION WITH LADDER</b>		
This Section may be used with all Lead types. (Similar to H).	7200051 1380 lbs.	7400025 2652 lbs.
<b>10 FT. INTERMEDIATE SECTION WITH LADDER</b>		
This Section may be used with all Lead types. (Similar to H).	7200036 840 lbs.	7400026 1391 lbs.
<b>7 FT. INTERMEDIATE SECTION WITH LADDER</b>		
This Section may be used with all Lead types. (Similar to H).	7200037 569 lbs.	7400027 1115 lbs.

